

2025

MULE 4000 TRANS™

Kawasaki

Let the Good Times Roll®



 BRIGHT WHITE



POWER

|                         |                                                                |
|-------------------------|----------------------------------------------------------------|
| Engine                  | 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled           |
| Displacement            | 617cc                                                          |
| Maximum Torque          | 34.7 lb-ft @ 2,500 rpm                                         |
| Bore x Stroke           | 76.0 x 68.0mm                                                  |
| Compression Ratio       | 10:3:1                                                         |
| Fuel System             | DFI® with 34mm Mikuni throttle body                            |
| Transmission            | Continuously Variable Transmission (CVT) with (H,N,R)          |
| Final Drive             | 2WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking          | No                                                             |
| Alternator Output (max) | 23 amp                                                         |

CAPABILITY

|                                 |                              |
|---------------------------------|------------------------------|
| Front Suspension / Wheel Travel | MacPherson Strut/3.9 in      |
| Rear Suspension / Wheel Travel  | DeDion Axle/2.8 in           |
| Front Tires                     | 23 x 11-10                   |
| Rear Tires                      | 23 x 11-10                   |
| Steering                        | Rack-and-pinion              |
| Park Brake Type                 | Independent, mechanical drum |
| Front Brakes                    | Drum                         |

|                              |                                                                     |
|------------------------------|---------------------------------------------------------------------|
| Rear Brakes                  | Drum                                                                |
| Ground Clearance             | 7.7 in                                                              |
| Fuel Capacity                | 6.3 gal                                                             |
| Turning Radius               | 12.8 ft                                                             |
| Cargo Bed Dimensions (LxWxH) | 50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-person) |
| Cargo Bed Load Capacity      | 800 lb (2-person) / 401 lb (4-person)                               |
| Payload Capacity             | 1,330 lb                                                            |
| Seating Capacity             | 2-4                                                                 |
| Towing Capacity              | 1,200 lb                                                            |
| Lighting                     | (2) Halogen headlights, (2) tail/brake lights                       |

DETAILS

|                |                                                                                                       |
|----------------|-------------------------------------------------------------------------------------------------------|
| Overall Length | 128.5 in                                                                                              |
| Overall Width  | 58.5 in                                                                                               |
| Overall Height | 75.8 in                                                                                               |
| Curb Weight    | 1,514.8 lb*                                                                                           |
| Wheelbase      | 85.2 in                                                                                               |
| Instruments    | Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter |
| Color Choices  | Bright White                                                                                          |
| Warranty       | Kawasaki STRONG 3-Year Limited Warranty                                                               |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ 4000/4010 and MULE 4000/4010 TRANS™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.