## **MULE PRO-DX™ EPS**









## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

**Maximum Torque** 38.3 lb-ft @ 2,400 rpm

74.0 x 77.0mm **Bore x Stroke** 

**Compression Ratio** 

23.5:1 Bosch in-line injection pump **Fuel System** 

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission** 

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** Yes

**Alternator Output** 

(max)

55 amp

## CAPABILITY

Double wishbone/8.7 in Front Suspension / **Wheel Travel** 

Rear Suspension / Double wishbone/8.5 in (L)/8.7 in (R) Wheel Travel

**Front Tires** 26 x 9-12 **Rear Tires** 26 x 11-12

Steering Electric Power Steering (EPS), Tilt steering

**Park Brake Type** Independent, mechanical disc

**Front Brakes** Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

Warranty

**Ground Clearance** 10.4 in **Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

**Cargo Bed Dimensions (LxWxH)** 

**Cargo Bed Load** 

Capacity

1,574 lb **Payload Capacity** 

**Seating Capacity** 3-person

**Towing Capacity** 2.000 lb

(2) Halogen headlights Lighting

54.1 x 53.7 x 11.0 in

999 lb

## **DETAILS**

**Overall Length** 133.3 in **Overall Width** 64.0 in

**Overall Height** 77.4 in

**Estimated Dry** 

Weight

1,781.6 lb\*\*

**Curb Weight** 1,858.8 lb\*

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

**Color Choices Bright White** 

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.