2025 MULE PRO-FXT[™] 1000 PLATINUM RANCH EDITION





METALLIC STARDUST WHITE

7.9 gal

16.0 ft

2,000 lb

140.2 in

64.0 in

80.9 in

(4) LED headlights



42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

1,616.3/1,263.5 lb CA Model

3-person (1 row), 6 person (2 row)

POWER

	Turning Radius	
Engine Displacement	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas 999cc	Cargo Bed Dimensions (LxWxH)
Maximum Torque Bore x Stroke	61.5 lb-ft @ 4,500 rpm 92.0 x 75.1mm	Cargo Bed Load Capacity
Compression Ratio	10.1:1	Payload Capacity Seating Capacity
Fuel System Transmission	DFI® with 38mm throttle body Continuously Variable Transmission (CVT) with (H,L,N,R)	Towing Capacity
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Lighting
Engine Braking	Yes	DETAILS
Alternator Output (max)	90 amp	Overall Length Overall Width

CAPABILITY

		Estimated Dry Weight	1,955.8/1,958.0 lb** CA Model
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Curb Weight	2,030.8/2,033.0 lb* CA Model
Rear Suspension /	Double wishbone/10.1 in	Wheelbase	92.3 in
Wheel Travel		Instruments	Multi-function display includes digital speedometer, fuel
Front Tires	26 x 9-12, radial		gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil
Rear Tires	26 x 11-12, radial		pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking
Wheel Type	Alloy		indicators, seatbelt reminder lamps
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering	Additional Features	Roof, Additional Front Cup Holders, WARN® VRX 45 Winch,
Park Brake Type	Independent, mechanical disc		Premium Seats, Premium Shoulder Pads, Self-Leveling Rear Suspension, Quad LED Headlights, Brush Guard, Headlight
Front Brakes	Dual disc, 2-piston caliper		Guards, Rear Bumper, Anti-cinch Seat Belts, Rearview Mirror, Additional Under Seat Storage Bin
Rear Brakes	Dual disc, 1-piston caliper	Color Choices	Metallic Stardust White
Ground Clearance	12.6 in (max), 11.6 in (std)	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Ground Clearance	12.6 in (max), 11.6 in (std)	Warranty	Kawasaki STRONG 3-Year Limited Warranty

Fuel Capacity

Overall Height

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.