UPDATED 2025

MULE PRO-FXT™ 820 EPS









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement

48.0 lb-ft @ 3,500 rpm **Maximum Torque**

Bore x Stroke 72.0 x 66.5mm

Compression Ratio

Fuel System DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Rear Brakes Dual disc, 1-piston caliper

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-Cargo Bed **Dimensions (LxWxH)**

person)

Cargo Bed Load

Capacity

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

1,616.3/1,263.5 lb CA Model **Payload Capacity**

Seating Capacity 3-person (1 row), 6 person (2 row)

2,000 lb **Towing Capacity**

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / Double wishbone / 8.7 in **Wheel Travel**

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26 x 9-12, radial **Rear Tires** 26 x 11-12, radial

Wheel Type

Steering Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

steering

Park Brake Type Independent, mechanical disc

Front Brakes Dual disc, 2-piston caliper

DETAILS

133.3 in **Overall Length**

Overall Width 64.0 in

Overall Height

Estimated Dry Weight 1,832.4/1,834.6 lb** CA Model

1,911.7/1,913.9 lb* CA Model **Curb Weight**

Wheelbase

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

Color Choices Timberline Green

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.