MULE SX™ 4x4









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 82.0 x 76.0mm

Compression Ratio 8.6:1

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output 22.9 amp

(max)

Front Brakes Drum

Rear Brakes Drum

Ground Clearance 6.7 in

Fuel Capacity 4.2 gal

Turning Radius 10.8 ft

Cargo Bed 35.6 x 40.9 x 9.6 in Dimensions (LxWxH)

Dillielisions (LAWAII)

Cargo Bed Load

Capacity

Payload Capacity 915 lb

399 lb

Seating Capacity 2

eating capacity 2

Towing Capacity 1,100 lb**

Lighting (2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / Wheel Travel

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires 24

24 x 9-10

Rear Tires 24 x 11-10

Steering Rack-and-pinion

Park Brake Type

Independent, mechanical drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.9 in

Curb Weight 1.031.9 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light

Color Choices Super Black, Grayish Blue

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



**Requires Optional Hitch

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.