
## NINJA® 1100SX ABS









Dual 300mm discs with radial-mount 4-piston

Intelligent anti-lock Brake System (KIBS)

monobloc calipers, Kawasaki Intelligent anti-lock

Single 260mm disc with single-piston caliper, Kawasaki

## **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 1,099cc

Bore x Stroke 77.0 x 59.0mm

Compression Ratio 11.8:1

Maximum 134.0 hp<sup>1</sup> @ 9,000 rpm Horsepower

Maximum Torque 83.2 lb-ft @ 7,600 rpm

Fuel System DFI® with 38mm Electronic Throttle Valves

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift with wet multi-disc manual Assist

& Slipper Clutch

Final Drive Sealed chain

**Electronic Rider** 

**Aids** 

Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-

**Enhanced Chassis Orientation Awareness** 

## Rear Brakes DETAILS

**Front Tire** 

Rear Tire

**Front Brakes** 

Frame Type Twin-spar aluminum

120/70-17

190/50-17

Brake System (KIBS)

Rake/Trail 24.0°/3.9 in

Overall Length 82.7 in

Overall Width 31.7 in

Overall Height 46.9 in/48.2 in w/ windshield high

**Ground Clearance** 5.3 in

Seat Height 32.3 in

Estimated Dry 471.9 lb\*\*

Weight

**Color Choices** 

Curb Weight 518.2 lb\*

Fuel Capacity 5.0 gal

Wheelbase 56.7 in

Special Features 4.3" All-digital TFT Instrumentation, All-LED lighting,

USB Type-C outlet, Smartphone Connectivity with Voice Command via RIDEOLOGY THE APP MOTORCYCLE

Metallic Carbon Gray/Metallic Diablo Black

## **PERFORMANCE**

Front Suspension / Wheel Travel

41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in

protouu, iii

Rear Suspension / Wheel Travel Horizontal back-link, gas-charged rear shock with rebound damping, remotely adjustable spring

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

preload/5.6 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.