
## NINJA H2® CARBON ABS









## **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

**Bore x Stroke** 76.0 x 55.0mm

**Compression Ratio** 8.5:1

Maximum 239.6 hp1 @ 11,500 rpm

Horsepower

**Maximum Torque** 104.9 lb-ft @ 11,000 rpm

**Fuel System** DFI® with 50mm throttle bodies (4) with dual injection;

Kawasaki Supercharger

Ignition TCBI with Digital Advance

**Transmission** 6-speed, return shift, dog-ring

**Final Drive** Sealed chain

**Electronic Rider Aids** Economical Riding Indicator, Kawasaki Cornering

Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift

& downshift), Öhlins Electronic Steering Damper

## **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Rear Suspension / **Wheel Travel** 

Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback reservoir, 24-way compression and rebound damping adjustability, 15-way spring preload adjustability, and top-

outspring/5.3 in

**Front Tire** 120/70-17

**Front Brakes** Dual 330mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo Stylema® calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

**Rear Brakes** Single 250mm disc with opposed 2-piston caliper,

200/55-17

Kawasaki Intelligent anti-lock Brake System (KIBS)

## **DETAILS**

**Rear Tire** 

**Frame Type** Trellis, high-tensile steel, with swingarm mounting plate

Rake/Trail 24.5° / 4.1 in **Overall Length** 82.1 in

**Overall Width** 30.3 in

**Overall Height** 44.3 in

**Ground Clearance** 5.1 in

**Seat Height** 32.5 in 480.7 lb\*\*

**Estimated Dry** Weight

**Curb Weight** 524.8 lb\*

**Fuel Capacity** 4.5 gal

Wheelbase

**Special Features** Supercharged engine, All-digital TFT color

Instrumentation, All-LED lighting, Carbon fiber, Highly Durable Paint, Serial number stamp, Smartphone

Connectivity via RIDEOLOGY THE APP

**Color Choices** Mirror Coated Matte Spark Black/Candy Flat Blazed Green

12 Month Limited Warranty Warranty

57.3 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of

many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.