## **UPDATED 2025**

# NINJA H2® SX SE ABS









#### **POWER**

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 11.2:1

Maximum 207.0 hp<sup>1</sup> @ 10,000 rpm Horsepower

Maximum Torque 101.0 lb-ft @ 8,500 rpm

Fuel System DFI® with 40mm throttle bodies (4); Kawasaki Supercharger

**Ignition** TCBI with Digital Advance

Transmission 6-speed, return shift, dog-ring

Final Drive Sealed chain

Economical Riding Indicator, Advanced Rider Assistance Systems (ARAS): Forward Collision Warning (FCW), Blind-Spot Detection (BSD), Adaptive Cruise Control (ACC). Vehicle Hold Assist (VHA), Kawasaki Electronic Control Suspension with Showa Skyhook Technology (KECS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (dual direction), IMU-Enhanced Chassis Orientation Awareness

## **PERFORMANCE**

**Electronic Rider Aids** 

Front Suspension / Wheel Travel

43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Wheel Travel

Uni-Trak®, Showa BFRC lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.5 inspring/5.3 in

**Rear Tire** 190/55-17

Front Brakes Dual 320mm semi-floating discs with dual radial-mount,

120/70-17

opposed 4-piston Brembo Stylema® calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

# **DETAILS**

**Front Tire** 

Frame Type Trellis, high-tensile steel, with swingarm mounting plate

Rake/Trail 24.7°/4.1 in

Overall Length 85.6 in

Overall Height 49.6 in

Overall Height 49.6 in

**Ground Clearance** 

Seat Height 32.9 in

Curb Weight 590.9 lb\*

Fuel Capacity 5.0 gal

Wheelbase 58.3 in

Special Features Supercharged engine, 6.5" Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, Kawasaki's

Intelligent Proximity Activation Start System (KIPASS),
Highly Durable Paint, Grip heaters, Tire Pressure Monitoring
System (TPMS), Smartphone Connectivity via Kawasaki SPIN

infotainment app

Color Choices Emerald Blazed Green/Metallic Diablo Black/Metallic Matte

Graphenesteel Gray

Warranty 12 Month Limited Warranty

5.1 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. @2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit hawaii.kawasaki.com for full product details.