

2025

# NINJA<sup>®</sup> ZX<sup>™</sup>-10R KRT EDITION

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



LIME GREEN/EBONY/PEARL BLIZZARD WHITE



## POWER

Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	13.0:1
Maximum Horsepower	196.0 hp <sup>1</sup> @ 11,500 rpm
Maximum Torque	83.9 lb-ft @ 11,300 rpm
Fuel System	DFI <sup>®</sup> , 47mm throttle bodies
Ignition	TCBI with electronic advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Öhlins Electronic Steering Damper, Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

## Rear Suspension / Wheel Travel

Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

## Front Tire

120/70 ZR17

## Rear Tire

190/55 ZR17

## Front Brakes

Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)

## Rear Brakes

Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)

## DETAILS

### Frame Type

Aluminum perimeter

### Rake/Trail

25.0°/4.1 in

### Overall Length

82.1 in

### Overall Width

29.5 in

### Overall Height

46.7 in

### Ground Clearance

5.3 in

### Seat Height

32.9 in

### Curb Weight

456.4 lb\* (ABS), 452.0 lb\* (non-ABS)

### Fuel Capacity

4.5 gal

### Wheelbase

57.1 in

### Special Features

4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP

### Color Choices

Lime Green/Ebony/Pearl Blizzard White

### Warranty

12 Month Limited Warranty

## PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted Showa Balance Free Fork (BFF), adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in
---------------------------------	---

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.