
NINJA® ZX™-6R KRT EDITION









POWER

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression Ratio | 12.9:1

Maximum 127.0 hp¹ @ 13,000 rpm Horsepower

Fuel System DFI® with 38mm Keihin throttle bodies (4) and oval

sub-throttles

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Ka

Aids

nic Rider

Kawasaki Traction Control (KTRC), Power Modes

(Full/Low), Kawasaki Intelligent anti-lock Brake

System (KIBS) (ABS only), Kawasaki Quick Shifter

(KQS) (upshift only)

PERFORMANCE

Front Suspension / Wheel Travel

41mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs/4.7 in

Rear Suspension / Wheel Travel Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring

preload/5.9 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes Dual semi-floating 310mm discs with dual radial-

mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

Rear Brakes Single 220mm petal discs with single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 23.5°/4.0 in

Overall Length 79.7 in

Overall Width 28.0 in

Overall Height 43.3 in

Ground Clearance 5.1 in

Seat Height 32.7 in

Curb Weight 436.6 lb* (ABS), 432.2 lb* (non-ABS) 50-State Model, 434.4 lb* (ABS), 430.0 lb* (non-ABS) 49-State Model

Fuel Capacity 4.5 gal

Wheelbase 55.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green/Ebony/Pearl Blizzard White

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

