RIDGE® CREW HVAC







12.9 gal

19.0 ft

2.500 lb

All-LED lighting

34.6 x 49.0 x 12.8 in

1.000/600 lb CA Model

1,444/1,290 lb CA Model

6-person (2 row), bench seats



POWER

4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled Engine

Displacement

Maximum Horsepower 92.0 hp1 @ 8,500 rpm **Maximum Torque** 65.8 lb-ft @ 5.500 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1

Fuel System FFI

TCBI with Digital Advance Ignition

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 4WD with locking rear differential, shaft

Engine Braking Yes

Alternator Output

(max)

85 amp

Electronic Rider Aids Power Modes, Economical Riding Indicator

DETAILS

Lighting

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel Frame

Overall Length 155.3 in **Overall Width** 64.0 in **Overall Height** 81.5 in

Estimated Dry Weight 2,368.2/2,370.4 lb** CA Model **Curb Weight** 2.478.4/2.480.6 lb* CA Model

Wheelbase 122.2 in

Instruments

Warranty

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance

reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water

temperature)

Additional Features

Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY

THE APP Powersports, USB ports, KQR™ system compatible

Color Choices Candy Persimmon Red

Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Rear Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Front Tires

Duro 27 x 9-14

Rear Tires Wheel Type Duro 27 x 11-14 14" Aluminum

Steering

Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes Rear Brakes

Dual hydraulic 249mm discs with two-piston calipers Dual hydraulic 249mm discs with single-piston calipers

Ground Clearance

13.2/13.8 in (max preload); 13.2 in CA Model

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.