RIDGE® XR CREW LIMITED HVAC









POWER

4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled Engine

Displacement

Maximum Horsepower 116.0 hp1 @ 8,500 rpm **Maximum Torque** 73.8 lb-ft @ 8.000 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1 **Fuel System**

TCBI with Digital Advance Ignition

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive

Engine Braking Yes

Alternator Output

(max)

Electronic Rider Aids Power Modes, Economical Riding Indicator

Selectable 4WD with locking front/rear differential, shaft

85 amp

CAPABILITY

Front Suspension / Long-Travel, Double Wishbone/12.7 in Wheel Travel

Rear Suspension /

Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Front Tires SUNF 30 x 10-14 **Rear Tires** SUNF 30 x 10-14

Wheel Type 14" Aluminum

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes Dual hydraulic 249mm discs with two-piston calipers

Rear Brakes Dual hydraulic 249mm discs with single-piston calipers

Ground Clearance 13.4/14.6 in (max preload); 13.4 in CA Model **Fuel Capacity** 12.9 gal **Turning Radius**

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

19.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,290/1,076 lb CA Model

5-person (2 row), bench seats

2.500 lb

All-LED lighting

DETAILS

Ladder type, tubular steel Frame

Overall Length 161.1 in **Overall Width** 64.0 in **Overall Height** 82.3 in

Estimated Dry Weight 2,513.7/2,515.9 lb** CA Model

Curb Weight 2.624.0/2.626.2 lb* CA Model

Wheelbase 122.2 in

Instruments

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water

temperature)

Additional Features

8" Garmin Tread®, WARN® VRX 45-S Powersport Winch, Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Fullcolor TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR^{TM} system

compatible

Color Choices Metallic Bluish Gray

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.