## TERYX® KRX4™ 1000 LIFTED EDITION







23.3 ft

351 lb

1,001 lb

N/A

14.6 x 33.1 x 9.1 in



## **POWER**

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled **Engine** 

**Displacement** 999cc

**Maximum Torque** 76.7 lb-ft @ 7,000 rpm

**Bore x Stroke** 92.0 x 75.1mm

**Compression Ratio** 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System** 

TCBI with Electronic Advance Ignition

**Starting System** 

**Transmission** Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive** 

**Engine Braking** 

## DETAILS

Lighting

**Turning Radius** 

**Cargo Bed Load** 

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

(LxWxH)

Capacity

**Cargo Bed Dimensions** 

Ladder type, tubular steel

**Overall Length** 160.4 in **Overall Width** 68.1 in **Overall Height** 76.6 in

2,231.1 lb\* / 2,233.3 lb\* CA Model **Curb Weight** 

Wheelbase 125 8 in

Multi-function digital meter with bar-style tachometer (2 Instruments

(2) LED headlights, (2) LED taillights, LED stoplight

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp

**Additional Features** Elevated snorkel intakes and CVT exhaust duct, Wide fender flares, Front Bumper, F/R Tow Hooks, Steel skid-plates w/ drain

holes, Rear view mirror, WARN® VRX 45-S Powersport Winch

**Color Choices** Lime Green/Super Black

6 Month Limited Warranty Warranty

## CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-

position adjustable compression damping/21.1 in

ITP Cryptid 32 x 10.00R15 6PR **Front Tires** 

ITP Cryptid 32 x 10.00R15 6PR **Rear Tires** 

Electric Power Steering (EPS) / rack-and-pinion Steering

Front Brakes Dual hydraulic discs with 2-piston calipers

**Rear Brakes** Dual hydraulic discs with single-piston calipers

**Ground Clearance** 14.8 in (max), 14.2 in (std)

**Fuel Capacity** 10.6 gal

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.