2025 **TERYX4**™









POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with (2) 36mm Mikuni throttle bodies

TCBI with Electronic Advance Ignition

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential,

shaft

Engine Braking Yes **Ground Clearance** 11.2 in

Fuel Capacity 7.9 gal **Turning Radius**

Cargo Bed 17.9 x 47.6 x 8.7 in

Dimensions (LxWxH)

Cargo Bed Load Capacity

249 lb

16.7 ft

Payload Capacity 1,109 lb

Seating Capacity

Towing Capacity 1,300 lb

Lighting (2) incandescent headlights, (2) LED taillights, LED

stoplight

CAPABILITY

Rear Suspension /

Wheel Travel

Double Wishbone; FOX Podium coil-over shocks with Front Suspension / **Wheel Travel** piggyback reservoir, adjustable preload and 24-way compression damping/8.0 in

Double Wishbone; FOX Podium coil-over shocks with

piggyback reservoir, adjustable preload and 24-way compression damping/8.3 in

Front Tires Maxxis® 26 x 9-12

Rear Tires Maxxis® 26 x 11-12

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

DETAILS

Steel Tube Double-X Reinforcement **Frame**

Overall Length 125.4 in **Overall Width** 60.0 in **Overall Height** 77.8 in

Curb Weight 1,605.2 lb* / 1,607.4 lb* CA Model

Wheelbase 85.6 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter

and parking-brake indicator, R/N/P/4WD, water temp

and low-oil-pressure indicators

Color Choices Neon Yellow/Super Black

Kawasaki STRONG 3-Year Limited Warranty Warranty



