VERSYS® 1100 SE ABS









POWER

Horsepower

Engine 4-stroke, in-line 4-cylinder, DOHC, liquid-cooled

Displacement 1.099cc

Bore x Stroke 77.0 x 59.0mm

Compression Ratio 11.8:1

Maximum 133.0 hp1 @ 9,000 rpm

Maximum Torque 82.5 lb-ft @ 7,600 rpm

Fuel System DFI® with 38mm throttle bodies (4)

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift with wet multi-disc manual Assist &

Slipper Clutch

Final Drive Chain

Electronic Rider Aids Economical Riding Indicator, Electronic Cruise Control,

Kawasaki TRaction Control (KTRC), Kawasaki Electronic Control Suspension (KECS), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis

Orientation Awareness

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/5.9 in

Rear Suspension / **Wheel Travel**

Horizontal back-link, Showa BFRC Lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.9 in

Front Tire 120/70-17

Rear Tire 180/55-17

Front Brakes Dual 310mm petal discs with radial-mount 4-piston

monobloc calipers, Kawasaki Intelligent anti-lock Brake

System (KIBS)

Rear Brakes Single 260mm petal disc with single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

DETAILS

Frame Type Twin-tube, aluminum

Rake/Trail 27.0°/4.0 in **Overall Length** 89.4 in **Overall Width**

Overall Height 60.2 in (windshield Hi) / 59.8 in (windshield Lo)

Ground Clearance 5.9 in

Seat Height 33.1 in

Estimated Dry 520.4 lb** (+20 lb w/ saddlebags) Weight

37.4 in

Curb Weight 571.1 lb* (+20 lb w/ saddlebags)

Fuel Capacity 5.5 gal

Wheelbase 59.8 in

Special Features Full-color TFT Instrumentation, All-LED lighting including

Cornering Lights, USB Type-C outlet, Adjustable windshield, Grip heaters and hand guards, ERGO-FIT®, Highly Durable Paint, Smartphone Connectivity with Voice

Command via RIDEOLOGY THE APP MOTORCYCLE

Color Choices Metallic Graphite Gray/Metallic Diablo Black

Warranty 24 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.