## **Z500 SE ABS**









calipers and ABS

Single 310mm semi-floating disc with 2-piston

## **POWER**

4-stroke, Parallel Twin, DOHC, liquid-cooled **Engine** 

Displacement 451cc

70.0 x 58.6mm

**Bore x Stroke** Compression

**Ratio** 

11.3:1

Maximum Horsepower 51.0 hp<sup>1</sup> @ 10,000 rpm

**Maximum Torque** 

31.7 lb-ft @ 7,500 rpm

**Fuel System** 

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Economical Riding Indicator, Anti-lock Brake

Aids

System (ABS)

## **PERFORMANCE**

Front Suspension / Wheel Travel

41mm hydraulic telescopic fork/4.7 in

Rear Suspension / **Wheel Travel** 

Horizontal back-link with adjustable spring

preload/5.1 in

**Front Tire** 

110/70-17

**Rear Tire** 

150/60-17

## Single 220mm disc with single-piston caliper and **DETAILS Frame Type** Trellis, high-tensile steel 24.5° / 3.6 in Rake/Trail **Overall Length** 78.5 in **Overall Width** 31.5 in **Overall Height** 43.3 in **Ground Clearance** 5.7 in **Seat Height** 30.9 in **Estimated Dry** 339.6 lb\*\* / 341.8 lb\*\* 50-State Model Weight **Curb Weight** 370.4 lb\* / 372.6 lb\* 50-State Model **Fuel Capacity** 3.7 gal Wheelbase 54.1 in **Special Features** ERGO-FIT®, All-LED lighting, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP, USB-C outlet **Color Choices** Candy Persimmon Red/Metallic Flat Spark Black/ Metallic Matte Graphenesteel Gray

12 Month Limited Warranty

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.

Warranty

**Front Brakes** 

**Rear Brakes**