Z650RS ABS







POWER

4-stroke, 2-cylinder, DOHC, liquid-cooled **Engine**

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

67.0 hp1 @ 8,000 rpm

Maximum Horsepower

Maximum Torque 48.5 lb-ft @ 6,700 rpm

10.8:1

DFI® with Keihin 36mm throttle bodies

Ignition

TCBI with Electronic Advance

Transmission

Fuel System

6-speed, return shift

Final Drive

Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System

PERFORMANCE

Front Suspension / Wheel Travel

41mm telescopic fork/4.9 in

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable preload,

swingarm/5.1 in

Front Tire 120/70-17

Rear Tire 160/60-17

Front Brakes Dual 300mm petal-style discs with two-piston

calipers and ABS

Rear Brakes Single 220mm petal-style disc and ABS

DETAILS

Trellis, high tensile steel **Frame Type**

Rake/Trail 24.0°/3.9 in

Overall Length 81.3 in

Overall Width 31.5 in

Overall Height 43.9 in

Ground Clearance 4.9 in

Seat Height 31.5 in

Estimated Dry

Weight

Fuel Capacity

383.7 lb**

412.3 lb*

3.2 gal

Curb Weight

Wheelbase 55.3 in

Color Choices Ebony

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.





influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.