

# NEW 2026 KX™112

**Kawasaki**  
Let the Good Times Roll®



 LIME GREEN



## POWER

|                          |  |
|--------------------------|--|
| <b>Engine</b>            | 2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled |
| <b>Displacement</b>      | 112cc  |
| <b>Bore x Stroke</b>     | 52.5 x 51.6mm  |
| <b>Compression Ratio</b> | 9.9:1 (low speed) / 8.6:1 (high speed)                                   |
| <b>Fuel System</b>       | 28mm Keihin carburetor   |
| <b>Ignition</b>          | CDI with digital advance   |
| <b>Transmission</b>      | 6-speed, return shift, with wet multi-disc manual clutch                 |
| <b>Final Drive</b>       | Chain  |

|                     |  |
|---------------------|--|
| <b>Rear Tire</b>    | 90/100-16  |
| <b>Front Brakes</b> | Single 240mm petal disc with dual-piston caliper   |
| <b>Rear Brakes</b>  | Single 220mm petal disc with single-piston caliper |

## PERFORMANCE

|  |  |
|--|--|
| <b>Front Suspension / Wheel Travel</b> | 43mm inverted fork with adjustable compression and rebound damping/10.8 in   |
| <b>Rear Suspension / Wheel Travel</b>  | Uni-Trak® single shock with adjustable dual-range (high-low-speed) compression and rebound damping, plus adjustable spring preload/12.0 in |
| <b>Front Tire</b>                      | 70/100-19  |

## DETAILS

|                         |                                    |
|-------------------------|------------------------------------|
| <b>Frame Type</b>       | Perimeter, high-tensile steel      |
| <b>Rake/Trail</b>       | 29.2° / 4.6 in                     |
| <b>Overall Length</b>   | 76.2 in                            |
| <b>Overall Width</b>    | 31.5 in                            |
| <b>Overall Height</b>   | 45.9 in                            |
| <b>Ground Clearance</b> | 13.0 in                            |
| <b>Seat Height</b>      | 34.1 in                            |
| <b>Curb Weight</b>      | 164.9 lb* without fuel / 172.8 lb* |
| <b>Fuel Capacity</b>    | 1.32 gal                           |
| <b>Wheelbase</b>        | 51.6 in                            |
| <b>Special Features</b> | ERGO-FIT®                          |
| <b>Color Choices</b>    | Lime Green                         |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [hawaii.kawasaki.com](http://hawaii.kawasaki.com) for full product details.