

2026

MULE PRO-DXT™ EPS

Kawasaki

Let the Good Times Roll®



 SUPER BLACK



POWER		Ground Clearance	10.2 in
Engine	4-stroke, 3-cylinder, OHV, liquid-cooled, diesel	Fuel Capacity	7.9 gal
Displacement	993cc	Turning Radius	16.0 ft
Maximum Horsepower	24.0 hp ¹ @ 3,600 rpm	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Maximum Torque	38.3 lb-ft @ 2,400 rpm	Cargo Bed Load Capacity	999 lb (3-person) / 350 lb (6-person)
Bore x Stroke	74.0 x 77.0mm	Payload Capacity	1,574 lb
Compression Ratio	23.5:1	Seating Capacity	3-person (1-row), 6-person (2-row)
Fuel System	Bosch in-line injection pump	Towing Capacity	2,000 lb
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Lighting	(2) Halogen headlights
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	DETAILS	
Engine Braking	Yes		
Alternator Output (max)	55 amp	Overall Length	133.3 in
CAPABILITY		Overall Width	64.0 in
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Overall Height	77.6 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L)/8.7 in (R)	Estimated Dry Weight	1,898.5 lb**
Front Tires	26 x 9-12	Curb Weight	1,984.5 lb*
Rear Tires	26 x 11-12	Wheelbase	92.3 in
Steering	Electric Power Steering (EPS), Tilt steering	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Park Brake Type	Independent, mechanical disc	Additional Features	Roof, Horn, Universal Key, High Visibility Orange Seatbelts
Front Brakes	Dual disc, 2-piston caliper	Color Choices	Super Black
Rear Brakes	Dual disc, 1-piston caliper	Warranty	Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.