



2026 MULE SX™

Kawasaki
Let the Good Times Roll®



-  GRAYISH BLUE
-  SUPER BLACK



POWER

Engine	4-stroke, single-cylinder, OHV, air-cooled
Displacement	401cc
Maximum Horsepower	12.3 hp ¹ @ 3,800 rpm
Maximum Torque	20.6 lb-ft @ 2,200 rpm
Bore x Stroke	82.0 x 76.0mm
Compression Ratio	8.3:1
Fuel System	Nikki 6C1026 carburetor
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	2WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	17 amp

Front Brakes	Drum
Rear Brakes	Drum
Ground Clearance	6.1 in
Fuel Capacity	4.2 gal
Turning Radius	10.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Load Capacity	399 lb
Payload Capacity	926 lb
Seating Capacity	2
Towing Capacity	1,100 lb ^{***}
Lighting	(2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / Wheel Travel	MacPherson Strut/3.1 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in
Front Tires	22 x 9-10
Rear Tires	22 x 11-10
Steering	Rack-and-pinion
Park Brake Type	Independent, mechanical drum

DETAILS

Overall Length	106.7 in
Overall Width	52.6 in
Overall Height	70.1 in
Estimated Dry Weight	927.9 lb ^{**}
Curb Weight	967.6 lb [*]
Wheelbase	70.1 in
Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
Color Choices	Grayish Blue, Super Black

Scan with camera to view videos, key features and more.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{***}Requires optional hitch.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.